

| Product Data Sheet                         |                                      | SLn Max   |                |                |        |
|--|--------------------------------------|---|----------------|----------------|--------|
| Model                                      | SLn MAX - 600                        | SLn MAX - 750   | SLn MAX - 1000 | SLn MAX - 1100 |        |
| Type                                       | Double Side - Single Side            |   |                |                |        |
| Cleaning Rollers                           | Designed and Manufactured in the UK  |   |                |                |        |
| Construction                               | Designed in the UK                   |   |                |                |        |
| Machine Covers                             | Brushed Stainless Steel              |   |                |                |        |
| Machine parts                              | Aluminium - Stainless Steel - Delrin |   |                |                |        |
| Motors                                     | N/A                                  |   |                |                |        |
| Controls " Host Line " Line Running Signal | 24v DC                               |   |                |                |        |
| Software                                   | N/A                                  |   |                |                |        |
| Anti Static System                         | SIMCO Netherlands                    |   |                |                |        |
| Anti Static Bar                            | 1 x MEB or 2 x MEB                   |   |                |                |        |
| Pneumatics                                 | SMC                                  |   |                |                |        |
| Power Supply Unit                          | N/A                                  |   |                |                |        |
| Bearings                                   | SKF Japan                            |   |                |                |        |
| Effective Cleaning width                   | 620mm                                | 762mm   | 1000mm         | 1100mm         |        |
| Services                                   |                                      |   |                |                |        |
|  | Electrical Machine                   | 24v DC / 110vAC / 230vAC                                |                |                |        |
|  | Static Transformer                   | 110 / 230v AC 50/60Hz                                   |                |                |        |
|  | Power consumption - Machine          | 0.4 Watts / 0.97 Watts / 1.6 Watts                      |                |                |        |
|  | Power consumption - Static           | 55 Watts  |                |                |        |
|  | Air Pressure                         | 5 - 7 bar   |                |                |        |
|  | Air Pipe                             | 4mm OD  |                |                |        |
|  | Air Quality                          | Oil FreeDry   |                |                |        |
|  | Air Consumption                      | 0.157000L/Cycle   |                |                |        |
| Cleaning Rollers x 1 or x 2                |                                      |   |                |                |        |
|  | Base Material                        | Nanocleen - Urethane - 55Å                              |                |                |        |
|  |                                      | Film - Silicone - 35Å                                   |                |                |        |
|  |                                      | Panel - Silicone - 25Å                                  |                |                |        |
|  |                                      | Ultracleen - Silicone - 60Å                             |                |                |        |
|  |                                      | UTF - Silicone - 25Å                                    |                |                |        |
|  | AREP                                 | Adhesive Roll Eco Paper                                 |                |                |        |
|  | AREF                                 | Adhesive Roll Eco Film                                  |                |                |        |
|  | Overall Standard                     | ISO 6123 Class A - Part 1 - 2 - 3                       |                |                |        |
|  | Straightness                         | 0.1mm/m   |                |                |        |
|  | Roller Diameter                      | Ø 55mm  |                |                |        |
|  | Construction                         | Aluminium Tube & Stainless Steel Spigots                |                |                |        |
| Adhesive Rolls x 1 or x 2                  |                                      |   |                |                |        |
|  | Base Material                        | ECO -Moisture Stable Paper - Temp - Max 120°C / Min 5°C |                |                |        |
|  |                                      | ECO - Polypropylene - Temp - Max 120°C / Min 5°C        |                |                |        |
|  |                                      | Water Based Acrylic Adhesive                            |                |                |        |
|  | Diameters - Ø                        | ID - 76mm / OD - 100mm                                  |                |                |        |
| Machine Weight - DS Unit Data              |                                      |   |                |                |        |
|  |                                      | 7.1Kg   | 9Kg            | 12KG           | 13.2Kg |
| Load Per Standing Foot                     | N/A                                  |   |                |                |        |
| Pass Height                                | N/A                                  |   |                |                |        |
| Operation                                  |                                      |   |                |                |        |
|  | Mode                                 | N/A   |                |                |        |
|  | Flow direction                       | L - R or R - L  |                |                |        |
|  | Speed Range                          | 0.1 - 150m/min  |                |                |        |
|  | Speed Accuracy                       | Web Driven  |                |                |        |
| Mounting Options                           |                                      |   |                |                |        |
|  |                                      | Standard Mounting Brackets                              |                |                |        |
| Diverter Roller Options " DS Unit "        | Not Available                        |   |                |                |        |
| Diverter Roller Options " SS Unit "        | Not Available                        |   |                |                |        |