









No. 7540-00 HAIR HYGROMETER WITH GLASS THERMOMETER

SPECIFICATIONS

Min. graduation:

Sensors: Human hair bundle for humidity Glass thermometer for temperature

20 to 100%rh for humidity

Measuring range: -10 to 50°C for temperature

1%rh for humidity

2°C for temperature

±3%rh (40 to 80%rh, 15 to 25°C) Accuracy:

±5%rh (other range) ±2°C for temperature

Dimensions: 150 mm dia. x 40 (D) mm

Approx. 280 g Weight:

Accessories Test result, English manual

No. 7542-00 HYGROMETER WITH DIGITALTHERMOMETER

SPECIFICATIONS

Human hair bundle for humidity Sensors:

> Thermistor for temperature 20 to 100%rh for humidity

Measuring range: 0 to 50°C for temperature

Min. graduation: 2%rh for humidity

0.1°C for temperature

Accuracy: ±4%rh (40 to 80%rh, 15 to 25°C)

±7%rh (other range) ±1°C (0 to 40°C) ±2°C (other range)

Dimensions: 135 mm dia. x 33 (D) mm

Approx. 230 g Weight:

Bracket (160 mm dia. x 4 (D) mm), Accessories: AA battery x 2, English manual

No. 7562-00 HYGROTHERMOMETER MODEL PALMA II

SPECIFICATIONS

Sensors: Synthetic hair for humidity

Glass thermometer for temperature 20 to 99%rh for humidity Measuring range:

-10 to 50°C for temperature

Min. graduation: 1%rh for humidity

5°C for temperature

±4%rh (40 to 80%rh, 15 to 25°C) Accuracy:

±8%rh (other range) 95 mm dia. x 18 (D) mm

Dimensions:

Weight: Approx. 100 g Accessory English manual

No. 1013-00 THERMOHYGROMETER MODEL TH-300

SPECIFICATIONS

Sensors: Coil for humidity

Bimetallic strip for temperature

20 to 100%rh for humidity Measuring range:

-30 to 50°C for temperature

5%rh for humidity Min. graduation: 2°C for temperature

±5%rh (40 to 70%rh, 15 to 25°C) Accuracy:

±8%rh (other range) ±2°C for temperature

Dimensions: 285 (W) x 285 (H) x 35 (D) mm

Approx. 750 g Weight: Accessory English manual

No. 1074-00 DIGITAL THERMOHYGROMETER MODEL PC-5400TRH

SPECIFICATIONS

Sensors: Electric resistance change type for humidity

Thermistor for temperature

Measuring range: 20.0 to 95.0%rh for humidity 0.0 to 50.0°C for temperature

±5%rh (40 to 70%rh, 20 to 30°C)

Accuracy:

±8%rh (other than above) ±1.0°C (10 to 40°C) ±1.5°C (other range)

Dimensions: 225 (W) x 165 (H) x 25 (D) mm Approx. 480 g (includes batteries) Weight:

AA manganese battery (R6P) x 3, English manual Accessories: