

• AS862A Infrared Thermometer



Product No.: AS862A

Introduction: The most basic design consists of a lens to focus the infrared (IR) energy on to a detector.

FEATURES

The most basic design consists of a lens to focus the infrared (IR) energy on to a detector, which converts the energy to an electrical signal that can be displayed in units of temperature after being compensated for ambient temperature variation. Infrared Thermometers allow users to measure temperature in applications where conventional sensors cannot be employed. Specifically, in cases dealing with moving objects (i.e., rollers, moving machinery, or a conveyor belt), or where non-contact measurements are required because of contamination or hazardous reasons (such as high voltage), where distances are too great, or where the temperatures to be measured are too high for thermocouples or other contact sensor.

SPECIFICATIONS

| | |
|----------------------------|---------------------------|
| Temperature Range | -50°C~900°C(-58°F~1652°F) |
| Accuracy | ±2%or±2°C |
| Distance Spot Ratio | 12:1 |
| Emissivity | 0.10~1.00 adjustable |
| Resolution | 0.1°Cor 0.1°F(<1000°C) |
| Wavelength & Response Time | (8-14) μm &500ms |
| Repeatability | ±1%or±1°C |

| | |
|----------------------|---|
| °C/°F Selection | √ |
| Data Hold Function | √ |
| Laser Target Pointer | √ |
| Backlight Display | √ |
| Auto Power Off | √ |

PACKING INFORMATION

| | |
|------------------------------|--------------|
| Power | 9V battery |
| Product Net Weight | 170g |
| Product Size | 175*100*49mm |
| Packing Style | Gift box |
| Standard Quantity Per Carton | 24 |
| Standard Carton Size | 46*45.5*55cm |
| Standard Carton Gross Weight | 19.5KG |
