



# AF-6500 Platinum Pro Floor Finish

Urethane enhanced Platinum Pro™ AF-6500 Floor Finish is the ultimate protection against ESD events.

Flooring applied with Platinum Pro™ AF-6500 has ESD protection, safety, gloss, and are easy to maintain.

Using the longest lasting and highest performance available, Platinum Pro™ AF-6800 immediately reduces the cost of maintenance and increases ESD protection.



## Benefits

<b>Static Dissipative</b>	Protects devices from damage and workers from explosion/shock
<b>Low VOC</b>	Regulatory conformance/personnel safety
<b>High Abrasion</b>	Long lasting, reduces repetitive application
<b>High Gloss</b>	Aesthetically appealing "wet look"
<b>Low Tribogeneration</b>	Eliminates damage to devices
<b>UL Listed</b>	Slip resistant
<b>No Formaldehyde/ Phthalates</b>	Safe to use
<b>No Alkalis/Acids</b>	Safe to use
<b>Water Based</b>	Biodegradable/non-flammable/low odor



FLOOR COATING AND FINISHING MATERIAL CLASSIFIED BY UNDERWRITERS LABORATORIES, INC.® AS TO SLIP RESISTANCE ONLY



## Safety Information

Does not contain:

Glycol Ether DE	CAS# 111-90-0
Formaldehyde	CAS#50-00-0
Dibutyl Phthalate	CAS#87074-2

Health .....	1
Flammability .....	0
Reactivity .....	0
Personal Protection .....	B

**Warranty:** Static Solutions expressly warrants that for a period of 1 year from the date of purchase any Static Solutions product will be free of defects in materials and will function within its specifications. Within the warranty period, the product will be repaired or replaced at Static Solutions option with no cost to the customer as long as Static Solutions receives notice during the warranty period. Defective products must be shipped prepaid to Static Solutions, Inc.'s factory. Call Static Solutions customer service at 978.310.7251 for a return authorization number. Include a copy of the invoice, packing slip, or other proof of purchase.

**Warranty Exclusion:** The foregoing express warranty is made in lieu of other product warranties express and implied, including merchantability and fitness for a particular purpose which are specifically or indirectly dis-claimed. The express warranty will not apply to defects or damage due to neglect, misuse, accidents, alterations, operator error, failure to properly maintain, follow instruction, or failure to clean or repair products.

**Limit of Warranty:** In no event will Static Solutions or seller be responsible or liable for special, incidental or consequential losses or damages, whether based on contract or the use of or inability to use the product. Before using the product users shall determine the suitability of the product for their intended use. The users assume all risk and liability whatsoever in connection therewith. Fulfillment of Static Solutions warranty obligations will be the customer's exclusive remedy and Static Solutions and seller's limit of liability for any breach of warranty or otherwise.

## Specifications

<b>Active Ingredients</b>	Proprietary
<b>Surface Resistance (RTT) ANSI/ESD S7.1-1994</b>	10 <sup>7</sup> -10 <sup>9</sup> Ohms@100 Volts
<b>Slip Resistance ASTM D2047-5</b>	0.5 Minimum (UL Listed)
<b>Electrostatic Decay Time EIA 5410.1</b>	0.1 Seconds
<b>% Solids</b>	20% +/- 0.5%
<b>pH</b>	8.0-9.0
<b>Free Ammonia</b>	None
<b>Free Alkali</b>	None
<b>Free Acid</b>	None
<b>Phosphates</b>	None
<b>Color</b>	Milky White
<b>Odor</b>	Mild
<b>Water Solubility</b>	100%
<b>Freeze/Thaw Stability</b>	3 Cycles
<b>Shelf Life</b>	1 Year
<b>Flash Point</b>	None
<b>Weight/Gallon</b>	8.6 lbs./gallon
<b>Biodegradable</b>	Yes
<b>VOC</b>	3.5%



43 Broad Street  
Hudson, MA 01749  
Tel: 978-310-7251  
Fax: 978-310-7146

Static Solutions Inc. only sells through distributors.  
Please call us at 978-310-7251  
Or log on to our website at [www.staticsolutions.com](http://www.staticsolutions.com),  
to find your local distributor.

For additional Ohm-Shield™ product literature,  
call or fax the Static Solutions, Inc. sales department

**DISTRIBUTED BY:**