



AF-6800 Conduct Coat Floor Finish

Description

Ohm-Shield™ AF-6800 protects the costly investment of conductive/dissipative flooring.

It protects floors from discoloring with a UV blocking formula while offering long lasting, high gloss, static dissipative properties. With low VOC level, this product is as safe as it is easy to use.



Application

- Designed for conductive/dissipative tiles
- High Abrasion resistance
- Static Dissipative - low VOC
- 10^5 - 10^9 ohms/sq. resistivity
- No formaldehyde, no phthalates
- High Adhesion
- May be used in clean rooms, pharmaceutical rooms, assembly areas
- Low tribogeneration
- Durable and Long Lasting
- High Abrasion resistance



SAFETY INFORMATION

Product has a low odor, low VOC solvent and safe surfactant system.

Does not contain:

Glycol Ether DE	CAS#	111-90-0
Formaldehyde	CAS#	50-00-0
Dibutyl Phthalate	CAS#	87-74-2

Health1
Flammability0
Reactivity0
Personal ProtectionB

UL listed

Warranty: Static Solutions expressly warrants that for a period of 1 year from the date of purchase any Static Solutions product will be free of defects in materials and will function within its specifications. Within the warranty period, the product will be repaired or replaced at Static Solutions option with no cost to the customer as long as Static Solutions receives notice during the warranty period. Defective products must be shipped prepaid to Static Solutions, Inc.'s factory. Call Static Solutions customer service at 978.310.7251 for a return authorization number. Include a copy of the invoice, packing slip, or other proof of purchase.

Warranty Exclusion: The foregoing express warranty is made in lieu of other product warranties express and implied, including merchantability and fitness for a particular purpose which are specifically or indirectly dis-claimed. The express warranty will not apply to defects or damage due to neglect, misuse, accidents, alterations, operator error, failure to properly maintain, follow instruction, or failure to clean or repair products.

Limit of Warranty: In no event will Static Solutions or seller be responsible or liable for special, incidental or consequential losses or damages, whether based on contract or the use of or inability to use the product. Before using the product users shall determine the suitability of the product for their intended use. The users assume all risk and liability whatsoever in connection therewith. Fulfillment of Static Solutions warranty obligations will be the customer's exclusive remedy and Static Solutions and seller's limit of liability for any breach of warranty or otherwise.



43 Broad Street
Hudson, MA 01749
Tel: 978-310-7251
Fax: 978-310-7146

Static Solutions Inc. only sells through distributors.
Please call us at 978-310-7251
Or log on to our website at www.staticsolutions.com,
to find your local distributor.

Specifications:

Surface Resistance (RTT)	10 ⁸ -10 ⁹ ohms/sq. @ 100 volts
Electrostatic	
Decay Time EIA 541	0.1 seconds
Slip Resistance	
ASTM-D2047-5	0.5 minimum
Percent Solids	19.0%+/- 0.5%
pH	8.0-9.0
Free Ammonia	None
Free Alkali	None
Free Acid	None
Phosphates	None
Color	Milky White (Dries Clear)
Odor	Mild
Solubility in Water	100%
Freeze/Thaw Stability	3 cycles
Shelf Life	1 year
Flash Point	None
Weight Per Gallon	8.6 lbs./gallon
Biodegradable	Yes
VOC	4.52%

For additional Ohm-Shield™ product literature,
call or fax the Static Solutions, Inc. sales department

DISTRIBUTED BY: