



Guardian™ Constant Monitors

- Guardian™ CM-1700 Monitors one wrist strap and one operator
- Guardian™ Plus- CM-1701 Monitors one wrist strap, one operator and one ESD mat
- Guardian™ Pro- CM-1702 Monitors two wrist straps and two operators

SPECIFICATIONS

- 100% continuous monitoring
- Works with standard one conductor wrist straps/cords
- New technology: capacitance/impedance hyper technology
- NIST calibration included with certificate
- Visual LED, audio piezo sound
- AC powered or 9 volt battery operated(on CM-1700)
- Off/on switch and 4.0 mm docking snap.
- Set points can be adjusted for impedance of wrist straps, capacitance of person and resistance of mats
- Induces no unsafe current or unsafe volts into the operator
- RoHS compliant
- Includes monitor, power supply, ground cord, and NIST certificate/sticker.

Guardian™-CM-1700- Monitors one wrist strap and one operator

- **Size:** 3" by 2.75" by 1"
- **Mounting:** hook/loop and screws
- **Safe limits:** Under 1.2 megohms. Impedance can be adjusted according to weight and size of operator.
- **Fail limits:** Over 1.3 megohms which can be adjusted
- **Visual alarm:** red-fail, pass-green
- **Audio alarm:** piezo buzzer
- **Operation:** Active when switch tuned on, wrist strap on operator and green LED is on. Inactive when power switch turned off, and cord on docking snap. Wrist strap and person is connected to ground even if monitor is turned off. Trigger impedance is not changed by a change of incoming voltage.
- **Power:** 110V or 220V or 9 Volt battery with low power battery LED
- **Socket:** Banana plug and 4.0 mm docking snap
- **Price:** 1-25: \$49.00. Call for volume discounts



Guardian™ Plus-CM-1701- Monitors one wrist strap, one operator and one ESD mat.

- **Size:** 3" by 2.75" by 1"
- **Mounting:** Hook/loop and screws
- **Safe limits:** Under 1.2 megohms
- **Fail limits:** Over 1.3 megohms which can be adjusted.
- **Visual alarm:** Red-fail, pass-green
- **Audio alarm:** Piezo buzzer
- **Operation:** Active when the power switch tuned on, wrist strap is on the operator and the green LED is displayed. Inactive when the power switch is turned off, and the ground cord is on the docking snap. Wrist strap is connected to the ground even if monitor is turned off. Trigger impedance is not changed by a change of incoming voltage
- **Power:** 110 volt or 220 volt power adapter
- **Socket:** Banana plug and 4.0 mm docking snap
- **Price:** \$70.00 each. Call for volume discounts



Guardian™ Pro- CM-1702- Two wrist straps and two operators

- **Size:** 3" by 3.75" by 1"
- **Mounting:** Hook/loop and screws
- **Safe limits:** Below 1.2 megohms. Trigger impedance can be adjusted according to the weight or size of the operator.
- **Fail limits:** Over 1.3 megohms
- **Visual alarm:** Red-fail, pass-green
- **Audio alarm:** Piezo buzzer
- **Operation:** Active when the power switch is tuned on ,wrist strap is on the operator and green LED is on. Inactive when power switch turned off, and cord is on the docking snap. The wrist straps are connected to ground automatically even when the equipment is turned off!! Trigger impedance is not affected by change of input voltage.
- **Power:** 110V or 220V
- **Socket:** Banana plug and two 4.0 mm docking snaps
- **Price:** \$115.00- call for volume discounts



Calibration of above is \$50.00 including a NIST certificate

Call for higher volumes and distributor pricing. These monitors work extremely well with Ultimat™ ESD rubber, Ohm-Stat™ WS-1020/1037 patented wrist straps and the Ohm-Stat™ CT-8900/8700 combination testers.

Warranty: Static Solutions expressly warrants that for a period of 1 year from the date of purchase any Static Solutions product will be free of defects in materials and will function within its specifications. Within the warranty period, the product will be repaired or replaced at Static Solutions option with no cost to the customer as long as Static Solutions receives notice during the warranty period. Defective products must be shipped prepaid to Static Solutions, Inc.'s factory. Call Static Solutions customer service at 978.310.7251 for a return authorization number. Include a copy of the invoice, packing slip, or other proof of purchase.

Warranty Exclusion: The foregoing express warranty is made in lieu of other product warranties express and implied, including merchantability and fitness for a particular purpose which are specifically or indirectly dis-claimed. The express warranty will not apply to defects or damage due to neglect, misuse, accidents, alterations, operator error, failure to properly maintain, follow instruction, or failure to clean or repair products.

Limit of Warranty: In no event will Static Solutions or seller be responsible or liable for special, incidental or consequential losses or damages, whether based on contract or the use of or inability to use the product. Before using the product users shall determine the suitability of the product for their intended use. The users assume all risk and liability whatsoever in connection therewith. Fulfillment of Static Solutions warranty obligations will be the customer's exclusive remedy and Static Solutions and seller's limit of liability for any breach of warranty or otherwise.

**Static Solutions
Inc.** 43 Broad Street
Hudson, MA 01749
Tel: 978-310-7251
Fax: 978-310-7146

*For additional Ohm-Shield™ product literature,
call or fax the Static Solutions, Inc. sales department*

DISTRIBUTED BY:

Static Solutions Inc. only sells through distributors.
Please call us at 978-310-7251
Or log on to our website at www.staticsolutions.com,
to find your local distributor.

Ohm-Shield is a trademark of Static Solutions, Inc. ©2015 Static Solutions, Inc.
All specifications subject to change without notice. Printed in USA 1/1/15