

# TI175|TI395

## Thermal Imaging Cameras for Electricity & Industry Application

**ULIRVISION TI175|TI395** are affordable, easy-to-operate and high-performance thermal imaging cameras that offer accurate temperature measurements at safe distances.

**TI175|TI395** have a wide range of temperature measurements to satisfy a variety of thermograph applications. They are special electricity and industry applications.

### Features

---

Excellent thermal image and high accuracy temperature measurement

---

3.2", 270° rotatable and foldable LCD

---

Multi-mode for temp. measurement, max./min./avg temp, auto tracking, isotherms analysis

---

Tiny size, light weight 400g

---

Multi-lens for option

---

Fusion and overlay of the thermal image & visible image

---

### Applications

---

Building Diagnostics

---

Electrical/Mechanical Inspection

---

Research & Development

---

Automation Applications

---

Preventative & Predictive Maintenance

---



ULIRVISION

## Technical Specifications

Item	TI175	TI395
<b>Detector Data</b>		
Type	Uncooled FPA	
IR resolution	160×120	384×288
Pixel pitch	17μm	
Spectral range	7.5~14μm	
NETD/Sensitivity	70mK	
<b>Lens</b>		
FOV/Minimum imaging distance	24°×18°/15cm	24°×18°/30cm
IFOV	2.3mrad	1.2mrad
Focus	Auto/Motor	
Lens(Optional)	45°×34°/15cm、12°×9°/1m	
<b>Image Performance</b>		
Display	3.2",270° tiltable LCD,800×480 pixels	
Visual camera	3.0 mega pixel	
Frequency	50Hz/60Hz	
Zoom	1X~4X continuous	1X~8X continuous
Color palettes	12 palettes(including iron, rainbow, white hot and black hot etc.)	
Contrast/brightness	Auto/Manual	
<b>Measurement</b>		
Temperature range	-20℃~+250℃(Standard) 200℃~+600℃(Optional)	
Measurement accuracy	±2℃/±2%(reading)	
Spotmeter	4 adjustable spots	
Line profile	Vertical/Horizontal	
Area	3 adjustable boxes with max./min./avg temperature value	
Isotherms analysis	Capture high/low temperature/interval	
Alarm	Voice, color	
Measurement correction	Auto/Manual	
Emissivity correction	Adjustable from 0.01 to 1.0 or selected from list of materials	
Background temperature correction	Auto	
Atmospheric transmissivity correction	Auto	
Setting function	Date/time, temperature unit °C/°F/K, language	
Languages	10 languages(English, French, Italian, German, Spanish, Portuguese, Russian, Korean, Japanese, Simplified Chinese & Traditional Chinese)	

<b>Image Storage</b>		
Storage type	Built-in flash, >700 images	Built-in flash card, up to >500 images
	8G SD card, up to >11200 images	8G SD card, up to >8000 images
Storage mode	Auto/Manual store image in frame	
Signal frame infrared image format	JPEG, with 14-Bit radiometric image	
Signal frame visible light image format	JPEG or stored with thermal image	
Voice annotation	40s voice record, stored with per image via built-in microphone	
Periodic image storage	User defined, 7s at least	
<b>Laser Point</b>		
Grade/Type	Class 2,1mW/635nmRed	
<b>Interfaces</b>		
Power interface	Yes	
SD card slot	Yes	
Video output	CVBS	
Audio output	Yes	
USB	USE2.0, radiometric images、 measurement data and voice are transferred to PC	
Tripod	1/4" -20	
<b>Power System</b>		
Battery type	Lithium battery	
Battery operation time	2h continuous	
External power	DC: 5V±5%	
Charging system	Intelligent charger or in camera	
Power saving	Yes	
<b>Environment Parameters</b>		
Operating temperature range	-20°C~+50°C	
Storage temperature range	-40°C~+70°C	
Humidity	≤95%(Non-condense)	
Vibration	2G(IEC60068-2-6)	
Shock	25G(IEC60068-2-29)	
Encapsulation	IP54(IEC60529)	
<b>Physical Data</b>		
Size	128mm×62mm×154mm	
Weight	≤0.4kg(with battery and standard lens)	
<b>Packing</b>		

# ULIRVISION

Standard	Thermal imaging camera with standard IR lens, 2 Li-ion batteries, battery charger, adapter, USB cable, SD card, card reader, software CD, warranty card, calibration certificate
Option	Laptop, SLR camera