



UT202A+ Digital clamp meter

- 1.Industrial electricity
- 2.Residential electricity
- 3.Air conditioning
- 4.Automobile

Specifications	Range	UT202A+
AC current (A)	600A	±(2%+10)
AC current frequency (Hz)	50Hz~100Hz	±(1%+5)
AC voltage (V)	600V	±(0.8%+5)
AC voltage frequency(Hz)	10Hz~10kHz	±(1%+5)
DC voltage (A)	600V	±(0.5%+2)
Resistance (Ω)	60MΩ	±(0.8%+2)
Capacitance (F)	60mF	±(4%+5)
Frequency (Hz)	10Hz~10MHz	±(0.1%+4)
Features		
Display count		6000
Auto range		√
Jaw opening		28mm
True RMS		√
NCV		√
Live wire test		√
Continuity test		√
Diode		√
MAX/MIN		√
Relative mode		√
Data hold		√
Low battery indication		√
Auto power off		√
General Characteristics		
Power	1.5V battery (R03) x 2	
Display	37mm x 25mm	
Product color	Red and grey	

Product net weight	248g
Product size	215mm x 63mm x 36mm
Standard individual packing	Gift box, Carring bag, English manual
Standard quantity per carton	40pcs
Standard carton measurement	485mm x 295mm x 385mm
Standard carton gross weight	17.3kg