









UT256A 200A True RMS Fork Meter

UT256 series are high reliable, true RMS fork meters. Its unique design allows users to measure current by simply moving the wire ofinterest inside the opening of the 'fork' past the labeled mark. With no mechanical parts, this meter bares no risk from any type of mechanical failure. operation.

Specifications		
Model	Range	UT256A
AC current (A)	200A	±(1.8%+2)
AC voltage (V)	1000V	±(1.2%+3)

DC voltage (V)	1000V	±(0.8%+3)	
Resistance (Ω)	60ΜΩ	±(1%+2)	
Frequency (Hz)	10~10kHz	±(0.1%+5)	
Features			
Display count		6000	
Auto range		√	
True RMS		√	
NCV		Tricolor	
Data hold		√	
LCD backlight		√	
Auto power off	About 15 minutes	√	
Continuity buzzer		√	
Low battery indication	≤2.4V	√	
Input protection		√	
Input impedance	≥10MΩ	√	
General Characteristics			
Power	1.5V battery (LR6) x 2	1.5V battery (LR6) x 2	
Display	35mm x 26mm	35mm x 26mm	
Product color	Red and grey	Red and grey	
Product net weight	251g; UT256B: 163.7g	251g; UT256B: 163.7g	
Product size	217mm x 58.8mm x 38.5mm	217mm x 58.8mm x 38.5mm	
Standard accessories	Batteries, test leads	Batteries, test leads	
Standard individual packing	Gift box, carrying bag, English	Gift box, carrying bag, English manual	
Standard quantity per carton	20pcs	20pcs	
Standard carton measurement	485mm x 310mm x 205mm	485mm x 310mm x 205mm	
Standard carton gross weight	9.5ka	9.5kg	