

Wöhler A 550 Flue Gas Analyzer



Technical Data

Oxygen concentration (O ₂) in flue gas	Display	Vol.-% referenced to dry flue gas
	Measurement principle	Electrochemical sensor
	Range	0...21 Vol.-%
	Accuracy	±0,3 Vol.-%
Carbon monoxide (CO _V 4.000 ppm) in flue gas	Display	Vol.-ppm referenced to dry flue gas
	Measurement principle	Electrochemical sensor, H ₂ -compensated
	Range	0...4.000 Vol.-ppm, resolution 1 Vol.-ppm
	Accuracy	±20 ppm (< 400 ppm), otherwise 5 % of measurement
Carbon monoxide (CO _V) in flue gas	Display	Vol.-ppm referenced to dry flue gas
	Measurement principle	Electrochemical sensor
	Range	0...35.000 Vol.-ppm, resolution 1 Vol.-ppm
	Accuracy	±100 ppm (< 1.000 ppm), otherwise 10 % of measurement (with H ₂ < 5 % of measurement)
Carbon monoxide (CO _{V,high}) in flue gas (optional)	Display	Vol.-ppm referenced to dry flue gas
	Measurement principle	Electrochemical sensor
	Range	0...100 Vol.-ppm, resolution 1 Vol.-ppm
	Accuracy	±100 ppm (< 1.000 ppm), otherwise 10 % of measurement (with H ₂ < 5 % of measurement)
Nitric oxide concentration (NO _x) in flue gas (optional)	Display	Vol.-ppm referenced to dry flue gas
	Measurement principle	Electrochemical sensor
	Range	0...3.000 Vol.-ppm (continuously up to 1.000)
	Resolution	1 Vol.-ppm
	Accuracy	±5 Vol.-ppm (< 100 ppm), otherwise 5 % of readin
Nitrogen dioxide concentration (NO ₂) in flue gas (optional)	Display	Vol.-ppm referenced to dry flue gas
	Measurement principle	Electrochemical sensor
	Range	0...1.000 Vol.-ppm (continuously up to 200), resolution 1 Vol.-ppm
	Accuracy	±5 Vol.-ppm (< 100 ppm), otherwise 5 % of measurement
Sulfur dioxide (SO ₂) in flue gas (optional)	Display	Vol.-ppm referenced to dry flue gas
	Measurement principle	Electrochemical sensor
	Range	0...5.000 Vol.-ppm, resolution 1 Vol.-ppm
	Accuracy	±10 Vol.-ppm (0...200 ppm), otherwise 5 % of measurement
Chimney draught/differential pressure (P _D) with 4 Pa-Test	Display	Pascal
	Measurement principle	Semiconductor membrane
	Range	0...±110 hPa, resolution 0,1 Pa (< 1.000 Pa), otherwise 1 Pa, with ventilation loss measurement 0.01 Pa
	Accuracy	0,3 Pa (< 10 Pa), otherwise 3 % of measurement, Drift < 0,2 Pa in 5 minutes
Chimney draught/differential pressure (P _D)	Display	Pascal
	Measurement principle	Semiconductor membrane
	Range	0...±110 hPa, resolution 0,1 Pa
	Accuracy	2 Pa (< 40 Pa), otherwise 5 % of measurement
Flue gas temperature (T _A)	Display	°C
	Measurement principle	Thermoelement (NiCr-Ni)
	Range	-20...800 °C, resolution 0,1 °C
	Accuracy	0...133 °C: ±2 °C, 133...800 °C: ±1,5 % of measurement
Combustion air temperature (T _L)	Display	°C
	Measurement principle	Thermocouple (NiCr-Ni)
	Range	-20...100 °C, resolution 0,1 °C
	Accuracy	±1 °C
Wood moisture	Display	Mass of water referenced to dry fuel mass
	Measurement principle	Electrical resistance measurement
	Range	10...40 %, resolution 0,1 %
	Accuracy	±40 % of measurement tested to VDI 4206 Part 4
Power supply	Lithium-Ion, rechargeable battery 3,6 V, 6.700 mAh, charges via USB	
Battery operating time	approx. 12 h (depends on operating status and display illumination)	
Storage temperature	-20...50 °C	
Operating temperature	5...40 °C maintain stated accuracy	
Weight	1.250 g	
Dimensions	220 x 160 x 55 mm (without probe)	
Length of cable-hose	1,7 m	

WÖHLER

Wöhler Technik GmbH
Headquarters Germany

Wöhler-Platz 1 · 33181 Bad Wünnenberg
www.woehler-international.com