# **Products for Industry**

Standard Electric Furnace

F0611

Item Code : 214142 Model : F0611

Page Top

**Product Summary** 

Specifications

Optional items

Same series products





# **Standard Electric Furnace (F0611)**

Contact Us

Printing

F0611

### **Product Summary**

RCF-free (alumina fiber) that complies with RCF regulations is used for the furnace chamber.

Features of Standard Electric Furnace (F0611)

#### **Features**

RCF-free, safe and secure

#### Features

Simple Operation

#### **Features**

Equipped with program operation and timer function

#### **Features**

Improved safety functions

#### **Features**

Uses R thermocouple

#### **Features**

Equipped with a variety of options

# **Specifications**

#### **Specifications**

Item Code	214142
Model	F0611
Operating temp. range	100 to 1,150°C
Temp. control accuracy	±2.0°C (at 1,150°C)
Max. temp. reaching time	Approx. 80min.
Exterior material	Chrome-free electro-galvanized steel plate, Chemical proof painting
Internal material	Alumina fiber
Sensor	R-thermocouple
Heater	Iron-chrome wire
Heater	3kW
Exhaust port	20 mm I.D. (upper part)
Cooling Fan Type	Axial fan motor
Temp. controller	PID control by microprocessor
Temp. setting/display method	Digital setting by▲/▼ keys / Digital display
Overheat protection	Integrated controller
Overheat protection set	Digital setting
Operation function	Fixed temp., program (6 modes 30 seg.×1, 15 seg.×2, 10 seg.×3)
Additional function	Calibration off-set, Power outage compensation
Timer	1min to 99hr59min and 999hr 50min digital setting, Auto start, Quick auto stop
Safe Device	Self diagnosis circuit (Abnormal temp. sensor, Auto overheat protection), Averheat protector, Avercurrent ELB
Accessories	1 exhaust cap, 1 thermal fuse
Internal dimensions (W×D×H mm)	250×350×205mm
External dimensions (W×D×H mm)	507×604×677mm
Remarks(dimensions)	17.5L
Power Source	Single Phase AC200V 16A

	Plug is not attached, Electric code length is 2m
Weight	52kg

#### **Maintenance and warranty**

Conditions: temperature and humidity: 23 deg.C+/-5 deg.C, 65%RH+/-20% (no load)

External dimensions do not include protrusions.

# **Optional items**







## Same series products





