



YUYANG INDUSTRIAL CO., LIMITED

China Manufacturer of Fire Testing Equipment

PVC Anti Corrosion Salt Spray Test Equipment Environmental Testing Chamber



- **Product Details:**

- Place of Origin: **China**
- Brand Name: **YUYANG**
- Certification: **GB/T 10587-2006GB/T 10125-1997 JIS-D0201H8502H8610K5400Z2371**
- Model Number: **YY1009**

- **Payment & Shipping Terms:**
- Minimum Order Quantity: **1 set**
- Price: **Negotiation**
- Packaging Details: **Plywood Box**
- Delivery Time: **15-20 work days**
- Payment Terms: **T/T L/C Western Union**
- Supply Ability: **2 sets per month**
- Share to :

Detailed Product Description

Product Name:	Environmental Test Chamber	Usage:	Salt Spray Test Equipment
Test Chamber:	NSS.ACSS 35°C±1°C/CASS 50°C±1°C	Saturated Air Cylinder:	NSS.ACSS 47°C±1°C/CASS 63°C±1°C
Dimensions:	108L, 270L, 600L, 1440L	Power Supply:	AC220V, 50/60HZ

PVC Anti-corrosion Salt Spray Test Equipment Environmental Test Chamber

Description:

This machine has a standardized test method to check corrosion resistance of coated samples. Salt spray test is an accelerated corrosion test that produces a corrosive attack to the coated samples in order to predict its suitability in use as a protective finish. The appearance of corrosion products (oxides) is evaluated after a period of time. Test duration depends on the corrosion resistance of the coating; the more corrosion resistant the coating is, the longer the period in testing without showing signs of corrosion. Different coatings have different behaviour in salt spray test and consequently, test duration will differ from one type of coating to another.

Design standard:

CNS:3627,3385,4159,7669,8886 ; JIS:D0201,H8502,H8610,K5400,Z2371;

ISO: 3768,3769,3770;ASTM: 8117,B268.

Specifications:

Model	LY-609-60	LY-609-90	LY-609-120	LY-609-200
Design standard	GB/T 10587-2006,GB/T 10125-1997, JIS-D0201,H8502,H8610,K5400,Z2371			
Test chamber capacity(L)	108L	270L	600L	1440L
Temperature	Test chamber	NSS.ACSS 35°C±1°C/CASS 50°C±1°C		
	Saturated air cylinder	NSS.ACSS 47°C±1°C/CASS 63°C±1°C		
Test chamber size LxWxD(cm)	60*45*40	90*60*50	120*100*50	200*120*60
Max capacity of test liquid(L)	15	25	40	40
Outside Volume LxWxD(cm)	107*60*118	141*88*128	190*130*140	270*150*150
Power	AC220V,10A	AC220V,15A	AC220V,30A	AC220V,30A

Our Service:

If you face any problems in future during testing process we promise we will give you a reply within 48 hours and solution provide within 3 working days. We can offer operation video and English operation manual. We can provide video-con.

1. Considerate Service Different countries plugs, manually change the-voltage from 110V to 380V, insurance indicator.

2. Excellent After sale Service:

12 months warranty. Besides, we can help you to repair your problem controller freely, even it's not from our factory. What you need to do is to send us the controller.

3. Commitment:

We will sign a letter of commitment while we sign the contract, which will improve your confidence to us.

4. Good Packaging:

Simulation Animatronic Customer Triceratops are covered with air bubble film before put them into the wooden case, which not only has good shock absorption, impact resistance, heat sealing and also has the advantages of nontoxic, odorless, moisture corrosion, good transparency etc.

5. Products within one year free warranty(exclude man-made damage and consumable). During this period, if the equipment breaks down, buyer should send relative fault information to our mailbox. We will provide workable fault resolution. If the condition is serious, buyer send back the equipment to our company. But the transport charge is paid by the buyer. We offer free maintain.

